SPIDER SECURITY PRODUCTS

PHYSICAL SECURITY REDEFINED.TM



PRODUCT DATASHEET

SPIDER RESISTOR PACKS

Part Number: 55P-05DP-resph

PRODUCT INFORMATION

Spider Resistor Packs – Key Attributes:

- What's inside? A single 120 Ohm Resistor, soldered to Two 22AWG stranded conductor wires.
- **Just The Right Length** 4 inch wires. Too much slack wastes time.
- **Easy Color Scheme** Simple Green & White Leads help avoid wiring errors. (Land them over the existing Data Lines color-for-color).
- Parallel-wire Design Makes it easier to tape.
- Twisted Pairs OSDP requires twisted wires.
- **Encapsulation** Protects the resistor components safely inside.
- Lifetime Warranty Have a bad pack? Just mail us back the bad ones for immediate replacement!

Home Run Conductors from the Access Control Panel Green Wire White Wire White Wire Green Wire The resistors should be installed both at the panel, and the furthest reader on the Spider OSDE OSDP data bus. Tan Wire Red/Grn Wire *Data wire colors may Data Wires from vary, depending on manufacturer

SPECIFICATIONS

Internal Components (Per Resistor Pack):

- (Qty 1) 120 Ohm [Tolerance ±2%] 1/4W Resistor
- 22 AWG Stranded Wires
 (4" from Shrink Tube to End Tips)

Ratings:

Maximum Volts: 30VAC/VDCMaximum Watts: 7.5WMaximum Amps: .25A



CRUCIAL INFO AT: WWW.SPIDER PROTECT.COM